

## CLAIMS

What is claimed is:

1. A radio frequency integrated circuit (RFIC) comprises:

5 transmitter section operably coupled to convert outbound baseband signals into outbound radio frequency (RF) signals;

receiver section operably coupled to convert inbound RF signals into inbound baseband signals, wherein the receiver section includes:

10

a low noise amplifier operably coupled to amplify the inbound RF signals to produce amplified inbound RF signals;

15

down-conversion module operably coupled to convert the amplified inbound RF signals into baseband in-phase components and quadrature components;

orthogonal-normalizing module operably coupled to:

20

obtain a first coefficient that is based on at least one of power of the baseband in-phase components, power of the baseband quadrature components, and cross-correlation between the baseband in-phase components and the baseband quadrature components;

25

obtain a second coefficient that is based on at least one of the power of the baseband in-phase components, the power of the baseband quadrature components, and the cross-correlation between the baseband in-phase components and the baseband quadrature components;

30

normalize an orthogonal relationship between the baseband in-phase components and the baseband quadrature components based on the first

coefficient and the second coefficient to produce normalized in-phase components and normalized quadrature components; and

5 baseband processor operably coupled to recapture data from the normalized in-phase and quadrature components.

2. The RFIC of claim 1, wherein the orthogonal-normalizing module comprises:

10 a first multiplier module operably coupled to multiple the baseband in-phase components with the first coefficient to produce the normalized in-phase components;

a second multiplier module operably coupled to multiple the baseband in-phase components with the second coefficient to produce the cross-correlation; and

15 a subtraction module operably coupled to subtract the cross-correlation from the baseband quadrature components to produce the normalized quadrature components.

3. The RFIC of claim 2, wherein the first multiplier module comprises:

20 a first plurality of shift registers operably coupled to produce a plurality of shifted representations of the baseband in-phase components;

switch matrix operably coupled to pass selected ones of the plurality of shifted representations of the baseband in-phase components and the baseband in-phase components based on the first coefficient; and  
25

an adder operably coupled to add the selected ones of the plurality of shifted representations of the baseband in-phase components and the baseband in-phase components to produce the normalized in-phase components.  
30

4. The RFIC of claim 2, wherein the second multiplier module comprises:

a first plurality of shift registers operably coupled to produce a plurality of shifted representations of the baseband in-phase components;

- 5 switch matrix operably coupled to pass selected ones of the plurality of shifted representations of the baseband in-phase components based on the second coefficient; and

an adder operably coupled to add the selected ones of the plurality of shifted  
10 representations of the baseband in-phase components to produce the cross-correlation.

5. The RFIC of claim 1, wherein the orthogonal-normalizing module comprises:

a first multiplier module operably coupled to multiply the baseband in-phase components  
15 with the second coefficient to produce the cross-correlation;

a subtraction module operably coupled to subtract the cross-correlation from the baseband quadrature components to produce phase adjusted quadrature components; and

20 a second multiplier module operably coupled to multiply the phase adjusted quadrature components with the first coefficient to produce the normalized quadrature components, wherein the baseband in-phase components are passed as the normalized in-phase components.

25 6. The RFIC of claim 1, wherein the orthogonal-normalizing module comprises:

a first programmable register for storing the first coefficient; and

a second programmable register for storing the second coefficient, wherein the first and  
30 second coefficients are determined by a trial and error manufacturing test.

7. The RFIC of claim 1, wherein the orthogonal-normalizing module comprises:

a full matrix multiply module operably coupled to multiply the baseband in-phase components and the baseband quadrature components with a coefficient matrix that includes the first and second coefficients to produce the normalized in-phase components and the normalized quadrature components.

8. The RFIC of claim 1, wherein the orthogonal-normalizing module further functions to:

measure local oscillation leakage power to produce a first power measurement;

provide a first magnitude signal to an in-phase portion of the receiver section and a zero magnitude signal to a quadrature portion of the receiver section;

measure power of the in-phase portion and power of the quadrature portion while processing the first magnitude signal and the zero magnitude signal, respectively, to produce a second power measurement;

provide the first magnitude signal to the quadrature portion of the receiver section and the zero magnitude signal to the in-phase portion of the receiver section;

measure the power of the in-phase portion and the power of the quadrature portion while processing the zero magnitude signal and the first magnitude signal, respectively, to produce a third power measurement;

determine a gain imbalance based on the first, second, and third power measurements;

provide a second magnitude signal to the in-phase portion and to the quadrature portion;

measure the power of the in-phase and quadrature portions while processing the second magnitude signal to produce a fourth power measurement;

5 provide the second magnitude signal to the in-phase portion and a negative second magnitude signal to the quadrature portion;

measure the power of the in-phase portion and the power of the quadrature portion while processing the second magnitude signal and the negative second magnitude signal, respectively, to produce a fifth power measurement; and

10

determine a phase imbalance based on the first, fourth, and fifth power measurements, wherein the gain imbalance and the phase imbalance correspond to the power of the baseband in-phase components, the power of the baseband quadrature components, and the cross-correlation between the baseband in-phase components and the baseband quadrature components to determine the first and second coefficients.

15

9. The RFIC of claim 1, wherein the orthogonal-normalizing module further functions to obtain the first and second coefficients by:

20 measuring in-phase signal level of the receiver section while processing a sine wave;

measuring quadrature signal level of the receiver section while processing the sine wave;

25

determining the power of the baseband in-phase components based on the in-phase signal level;

determining the power of the baseband quadrature components based on the quadrature signal level;

30

determining cross-correlation power based on the in-phase signal level and the quadrature signal level; and

determining the first and second coefficients based on the power of the baseband in-phase components, the of the baseband quadrature components, and the cross-correlation power.

5

10. The RFIC of claim 1, wherein the orthogonal-normalizing module normalizes the orthogonal relationship between the baseband in-phase components and the baseband quadrature components by:

10 selecting one of the baseband in-phase components and the baseband quadrature components as a reference component; and

normalizing another one of the baseband in-phase components and the baseband quadrature components to the reference component.

15

11. The RFIC of claim 1, wherein the orthogonal-normalizing module further functions to:

update the first and second coefficients to compensate for at least one of temperature variation and aging.

20

12. A radio frequency integrated circuit (RFIC) comprises:

transmitter section operably coupled to convert outbound baseband signals into outbound radio frequency (RF) signals;

5

receiver section operably coupled to convert inbound RF signals into inbound data, wherein the receiver section includes:

10

a low noise amplifier operably coupled to amplify the inbound RF signals to produce amplified inbound RF signals;

down-conversion module operably coupled to convert the amplified inbound RF signals into baseband in-phase components and quadrature components;

15

orthogonal-normalizing module including:

an in-phase power module operably coupled to determine power of the baseband in-phase components;

20

a quadrature power module operably coupled to determine power of the quadrature components;

25

a cross-correlation power module operably coupled to determine a cross-correlation power based on the baseband in-phase and quadrature components; and

30

normalizing module operably coupled to normalize the baseband in-phase components and the baseband quadrature components based on the power of the baseband in-phase components, the power of the baseband quadrature components, and the cross-correlation power to produce

normalized in-phase components and normalized quadrature components;  
and

5 baseband processor operably coupled to recapture the inbound data from the  
normalized in-phase and quadrature components.

13. The RFIC of claim 12, wherein the normalizing module comprises:

10 a coefficient module operably coupled to determine coefficients based on the power of  
the baseband in-phase components, the power of the baseband quadrature components,  
and the cross-correlation power, wherein the baseband in-phase components and the  
baseband quadrature components are normalized based on the coefficients.

14. The RFIC of claim 12, wherein the in-phase power module comprises:  
15

a multiplier operably coupled to square the baseband in-phase components to produce  
squared in-phase values; and

20 an accumulator operably coupled to accumulate the squared in-phase values for a  
predetermined period of time to produce the power of the baseband in-phase components.

15. The RFIC of claim 12, wherein the quadrature power module comprises:

25 a multiplier operably coupled to square the baseband quadrature components to produce  
squared quadrature values; and

an accumulator operably coupled to accumulate the squared quadrature values for a  
predetermined period of time to produce the power of the baseband quadrature  
components.

30

16. The RFIC of claim 12, wherein the cross-correlation power module comprises:



a multiplier operably coupled to multiply the baseband in-phase components and the baseband quadrature components to produce cross-correlation values; and

- 5 an accumulator operably coupled to accumulate the cross-correlation values for a predetermined period of time to produce the cross-correlation power.

17. A radio frequency integrated circuit (RFIC) comprises:

receiver section operably coupled to convert inbound radio frequency (RF) signals into inbound baseband signals;

5

transmitter section operably coupled to convert outbound data into outbound RF signals, wherein the transmitter section includes:

10

baseband processor operably coupled to convert the outbound data into the baseband in-phase components and baseband quadrature components;

orthogonal-normalizing module operably coupled to:

15

obtain a first coefficient that is based on at least one of a gain imbalance and phase imbalance;

obtain a second coefficient that is based on at least one of the gain imbalance and the phase imbalance;

20

normalize an orthogonal relationship between the baseband in-phase components and the baseband quadrature components based on the first coefficient and the second coefficient to produce normalized in-phase components and normalized quadrature components;

25

up-conversion module operably coupled to convert the normalized in-phase components and normalized quadrature components into RF signals; and

power amplifier operably coupled to amplify the RF signals to produce the outbound RF signals.

30

18. The RFIC of claim 17, wherein the orthogonal-normalizing module comprises:

a first multiplier module operably coupled to multiple the baseband in-phase components with the first coefficient to produce the normalized in-phase components;

- 5 a second multiplier module operably coupled to multiple the baseband in-phase components with the second coefficient to produce cross coupled in-phase components; and

a subtraction module operably coupled to subtract the cross coupled in-phase components  
10 from the baseband quadrature components to produce the normalized quadrature components.

19. The RFIC of claim 18, wherein the first multiplier module comprises:

- 15 a first plurality of shift registers operably coupled to produce a plurality of shifted representations of the baseband in-phase components;

switch matrix operably coupled to pass selected ones of the plurality of shifted representations of the baseband in-phase components and the baseband in-phase  
20 components based on the first coefficient; and

an adder operably coupled to add the selected ones of the plurality of shifted representations of the baseband in-phase components and the baseband in-phase components to produce the normalized in-phase components.

25

20. The RFIC of claim 18, wherein the second multiplier module comprises:

a first plurality of shift registers operably coupled to produce a plurality of shifted representations of the baseband in-phase components;

30

switch matrix operably coupled to pass selected ones of the plurality of shifted representations of the baseband in-phase components based on the second coefficient; and

- 5 an adder operably coupled to add the selected ones of the plurality of shifted representations of the baseband in-phase components to produce the cross coupled in-phase components.

21. The RFIC of claim 17, wherein the orthogonal-normalizing module comprises:

10

a first multiplier module operably coupled to multiply the baseband in-phase components with the second coefficient to produce cross coupled in-phase components;

a subtraction module operably coupled to subtract the cross coupled in-phase components  
15 from the baseband quadrature components to produce phase adjusted quadrature components; and

a second multiplier module operably coupled to multiply the phase adjusted quadrature components with the first coefficient to produce the normalized quadrature components,  
20 wherein the baseband in-phase components are passed as the normalized in-phase components.

22. The RFIC of claim 17, wherein the orthogonal-normalizing module comprises:

- 25 a first programmable register for storing the first coefficient; and

a second programmable register for storing the second coefficient, wherein the first and second coefficients are determined by a trail and error manufacturing test of the gain imbalance and the phase imbalance.

30

23. The RFIC of claim 17, wherein the orthogonal-normalizing module comprises:

a full matrix multiply module operably coupled to multiply the baseband in-phase components and the baseband quadrature components with a coefficient matrix that includes the first and second coefficients to produce the normalized in-phase components  
5 and the normalized quadrature components.

24. The RFIC of claim 17, wherein the orthogonal-normalizing module further functions to:

10 measure local oscillation leakage power to produce a first power measurement;

provide a first magnitude signal to an in-phase portion of the transmitter section and a zero magnitude signal to a quadrature portion of the transmitter section;

15 measure power of the in-phase portion and power of the quadrature portion while processing the first magnitude signal and the zero magnitude signal, respectively, to produce a second power measurement;

provide the first magnitude signal to the quadrature portion of the transmitter section and  
20 the zero magnitude signal to the in-phase portion of the transmitter section;

measure the power of the in-phase portion and the power of the quadrature portion while processing the zero magnitude signal and the first magnitude signal, respectively, to produce a third power measurement;

25 determine the gain imbalance based on the first, second, and third power measurements;

provide a second magnitude signal to the in-phase portion and to the quadrature portion;

30 measure the power of the in-phase and quadrature portions while processing the second magnitude signal to produce a fourth power measurement;

provide the second magnitude signal to the in-phase portion and a negative second magnitude signal to the quadrature portion;

- 5     measure the power of the in-phase portion and the power of the quadrature portion while processing the second magnitude signal and the negative second magnitude signal, respectively, to produce a fifth power measurement; and

determine the phase imbalance based on the first, fourth, and fifth power measurements.

10

25.     The RFIC of claim 17, wherein the orthogonal-normalizing module normalizes the orthogonal relationship between the baseband in-phase components and the baseband quadrature components by:

- 15     selecting one of the baseband in-phase components and the baseband quadrature components as a reference component; and

normalizing another one of the baseband in-phase components and the baseband quadrature components to the reference component.

20

26.     The RFIC of claim 17, wherein the orthogonal-normalizing module further functions to:

update the first and second coefficients to compensate for at least one of temperature variation and aging.

25

27. A method for orthogonal normalization of a radio frequency integrated circuit (RFIC), the method comprises:

determining phase imbalance and gain imbalance of a transmitter section of the RFIC;

5

normalizing baseband in-phase components and baseband quadrature components of the transmitter section based on the phase imbalance and the gain imbalance of the transmitter section;

10 coupling the transmitter section to a receiver section of the RFIC in a loop back configuration;

providing a test signal from the transmitter section to the receiver section;

15 determining power of baseband in-phase components, power of baseband quadrature components, and cross-correlation between the baseband in-phase components and the baseband quadrature components of the receiver section while processing the test signal; and

20 normalizing the baseband in-phase components and the baseband quadrature components of the receiver section based on the power of the baseband in-phase components, the power of the baseband quadrature components, and the cross-correlation between the baseband in-phase components and the baseband quadrature components.

25 28. The method of claim 27, wherein the normalizing the baseband in-phase components of the receiver section comprises:

multiplying the baseband in-phase components with the first coefficient to produce the normalized in-phase components;

30

multiplying the baseband in-phase components with the second coefficient to produce the cross-correlation; and

5 subtracting the cross-correlation from the baseband quadrature components to produce the normalized quadrature components.

29. The method of claim 27, wherein the determining phase imbalance and gain imbalance of a transmitter section comprises:

10 measuring local oscillation leakage power to produce a first power measurement;

providing a first magnitude signal to an in-phase portion of the transmitter section and a zero magnitude signal to a quadrature portion of the transmitter section;

15 measuring power of the in-phase portion and power of the quadrature portion while processing the first magnitude signal and the zero magnitude signal, respectively, to produce a second power measurement;

20 providing the first magnitude signal to the quadrature portion of the transmitter section and the zero magnitude signal to the in-phase portion of the transmitter section;

measuring the power of the in-phase portion and the power of the quadrature portion while processing the zero magnitude signal and the first magnitude signal, respectively, to produce a third power measurement;

25 determining the gain imbalance based on the first, second, and third power measurements;

30 providing a second magnitude signal to the in-phase portion and to the quadrature portion;



measuring the power of the in-phase and quadrature portions while processing the second magnitude signal to produce a fourth power measurement;

5 providing the second magnitude signal to the in-phase portion and a negative second magnitude signal to the quadrature portion;

measuring the power of the in-phase portion and the power of the quadrature portion while processing the second magnitude signal and the negative second magnitude signal, respectively, to produce a fifth power measurement; and

10

determining the phase imbalance based on the first, fourth, and fifth power measurements.

30. The method of claim 27, wherein the determining the power of baseband in-phase  
15 components, the power of baseband quadrature components, and the cross-correlation comprises:

measuring in-phase signal level of the receiver section while processing the test signal;

20 measuring quadrature signal level of the receiver section while processing the test signal;

determining the power of the baseband in-phase components based on the in-phase signal level;

25 determining the power of the baseband quadrature components based on the quadrature signal level; and

determining cross-correlation power based on the in-phase signal level and the quadrature signal level.

30

31. The method of claim 27 further comprises:

repeating the normalizing of the transmitter section and the receiver section to fine tune an orthogonal relationship between the baseband in-phase components and baseband quadrature components of the transmitter section and an orthogonal relationship between the baseband in-phase components and baseband quadrature components of the receiver section.

32. The method of claim 27 further comprises, in an ordered sequence:

10 coupling the transmitter section to the receiver section in the loop back configuration;

providing the test signal from the transmitter section to the receiver section;

15 determining the power of baseband in-phase components, the power of baseband quadrature components, and the cross-correlation between the baseband in-phase components and the baseband quadrature components of the receiver section while processing the test signal;

20 normalizing the baseband in-phase components and the baseband quadrature components of the receiver section based on the power of the baseband in-phase components, the power of the baseband quadrature components, and the cross-correlation between the baseband in-phase components and the baseband quadrature components;

25 determining the phase imbalance and the gain imbalance of the transmitter section;

normalizing baseband in-phase components and baseband quadrature components of the transmitter section based on the phase imbalance and the gain imbalance of the transmitter section; and

30 repeating the ordered sequence of normalizing of the receiver section and the transmitter section to fine tune an orthogonal relationship between the baseband in-phase

components and baseband quadrature components of the receiver section and an orthogonal relationship between the baseband in-phase components and baseband quadrature components of the transmitter section.